




<p>Integrated Amplifier a25.2 silver / black</p>		<ul style="list-style-type: none"> - Power 60W/8Ω, 2 x 75W/4Ω - S/N: ≥101dB - Frequency Range:10Hz -50kHz ±0.5dB - Distortion (THD+N): <0.002(1kHz) - Preamp out / Subwoofer connection - 5 analogue Inputs (Tape loop) - Headphone Output on front - Remote control for a25.2 and cd25.2 - Dimension: 8,5 x 43 x 35,5cm (HxWxD) 	<p>125.000Ft</p>
<p>Integrated Amplifier A50.2 silver / black</p>		<ul style="list-style-type: none"> - Power 100W/8Ω, - Preamp out / Subwoofer connection - 4 analogue Inputs (Tape loop), iPOD input - 1 MM/MC phono input - Dimension: 8,5 x 43 x 35,5cm (HxWxD) 	<p>299.000Ft</p>
<p>CD Player cd25.2 silver / black</p>		<ul style="list-style-type: none"> - Philips VAM1202/19 Drive - Burr-Brown PCM 1738 - 24-bit/192kHz DAC - Output: 2 digital, 1 coaxial, 1 optical - Remote control for a25.2 and cd25.2 - Dimension: 6,3 x 43 x 35,5cm (HxWxD) 	<p>169.000Ft</p>
<p>RDS Tuner t25.2 silver / black</p>		<ul style="list-style-type: none"> - am/fm RDS radio, 80 Memory stations - Remote control for a25.2, cd25.2 and t25.2 - Wave bands: AM 531-1602kHz, FM 87,5-108,0 MHz - Selectivity FM: 30dB - Sensivity FM: 46dB - Dimension: 6,3 x 43 x 35,5cm (HxWxD) 	<p>99.900Ft</p>
<p>CD Receiver Trio silver / black</p>		<ul style="list-style-type: none"> - Power 50W/8Ω, 2 x 65W/4Ω - Frequency Range:10Hz -50kHz ±0.5dB - Distortion (THD+N): <0.003(1kHz) - Preamp + Subwoofer Output - 4 analogue Inputs (Tape loop) + - 1 S-Video Input / Output - Headphone Output on front - A/B Speaker output - Dimensions: 8,5 x 43 x 35,5 (HxWxD) 	<p>199.000Ft</p>
<p>Phono-preamp pa.1.2 Black</p>		<ul style="list-style-type: none"> -high quality phono preamplifier - MM/MC loadable - external power supply 	<p>39.000Ft</p>
<p>Digital analog Converter dac25.2 silver/black</p>		<ul style="list-style-type: none"> -Digital-Analóg konverter -Elektro-Harmonix 6922 Tube output -Ti PCM1796 24bit, 192kHz DAC -reclocking und anti-jitter control system -8x oversampling digital filter -4 digital inputs: coax (s/pdif), opt., XLR,USB Dimensions: 9,5 x 21,6 x 34,3cm 	<p>199.000Ft</p>
<p>Turntable mmf-2.2 Black</p>		<ul style="list-style-type: none"> -high quality tonarm -Low noise belt -isolated motor -precide bronze bearing -music hall " Tracker " MM cartridge -Dimension: 43,2 x 33 x 11,5 cm 	<p>124.000Ft</p>

<p>Turntable</p> <p>mmf-5.1</p> <p>Black</p>		<ul style="list-style-type: none"> - Dual layer plinth construction - Low noise belt design - Separately isolated motor (33 / 45rpm) - Precision stainless steel main bearing sheathed in Teflon for noise free operation - Aluminium platter with soft felt mat - Metal screw clamp - Including Goldring "G1012" mm-cartridge 	<p>249.000Ft</p>
<p>Turntable</p> <p>mmf-7.1</p> <p>Black</p>		<ul style="list-style-type: none"> - Dual layer plinth construction - Carbon fibre tone arm - Separately isolated and decoupled motor - Precision stainless steel main bearing sheathed in Teflon for noise free operation - Non-resonant acrylic platter - Metal screw clamp - Adjustable tip toe feet, Level gauge - Including Goldring "Eroica H" mc cartridge 	<p>417.000Ft</p>
<p>High End Turntable</p> <p>mmf-9.1</p> <p>black</p>		<ul style="list-style-type: none"> - Triple layer plinth construction - High End Carbon fibre tone arm - Completely isolated and decoupled electronic speed control motor - Inverted ceramic main bearing for ultra quiet fluid operation - Non-resonant thick acrylic platter - Adjustable tip toe feet, Level gauge - Incl. Goldring "Eroica LX" mc cartridge 	<p>563.000Ft</p>